



GENERAL INFORMATION

The Secondary Seal is a rim mounted system suitable for floating roof tanks of all sizes storing all grades of crude and refined products.

DESIGN

The CPL5 Seal is designed to be installed whilst the tank is in service. The seal incorporates a compression plate, synthetic rubber wiper and vapour barrier membrane. The compression plate can be made from either galvanised steel or stainless steel.

The vapour barrier membrane is normally manufactured from polyurethane-coated nylon fabric with very low vapour permeability properties. PVC Nitrile, PTFE/Teflon or Firestop materials may be adopted depending of customers' requirements.

The seal design is such that all the fixings are on the outside of the seal; i.e. the tank shell side is completely smooth. The smooth outside surface of the seal ensures that the risk of damage is minimized if the roof is floating above the tank shell.

The seal can be fixed to either a vertical upstand or horizontal angle. The dimensions of the compression plate can be varied to suit a wide range of nominal rim spaces.

The wiper maintains approximately 65 mm contact with the wall of annular spaces

INSTALLATION

The CPL5 Secondary Seal can be easily installed with the tank in service as no hot work is required and the seal is simply bolted in position on top of the roof rim.

A double seal version of this design is also available.



TECHNICAL DATA

Rim Space: 200 mm $\pm$ 120 mm.

Aromatic Service: 100%

MATERIAL SPECIFICATION

Compression Plate: 1.6mm Galvanised Steel
1.5 mm Stainless Steel

Clamp Channels: Galvanised or Stainless Steel

Wiper: Synthetic rubber, high tensile strength, good wear resistance, excellent weathering.

Vapour Barrier: Polyurethane, PTFE, SC

Shunts: Stainless Steel

Typical Service Life : 10-20 years



Tank Aluminum
Cover

**TankSeal® CPL5: SECONDARY
COMPRESSION PLATE SEAL “L”**

www.tankaluminumcover.com

Email: customers@tankaluminumcover.com